

The4thware Industrial Server

4U Hot-Swappable Industrial Server for ODM Purpose

T4WT-TS46508



PRODUCT SPECIFICATION

Specification	
Dimensions (mm)	437.5mm x 650mm x 176.5mm, standard 19" rackmount chassis.
Materials	1.0mm SGCC Zinc-Coated Steel.
Backplane	6Gb/s MINI SAS backplane, with temperature control chipset. / 12Gb/s MINI SAS backplane, with temperature control chipset.
Driver bays	8 x 3.5" hot-swappable SATA (II or III) / SAS (II or III) 6Gb/s drive bays.
Cooling Fan	Standard quotation with 3pcs 12038H ball bearing fans.
PSU form factor	Standard PS2 power supply or redundant power supply.
M/B form factor	Support MAX 12" x 13" motherboard.
Expansion Slot	7 full-height PCI/PCIE expansion slots.
Connector	Two front accessible USB2.0 ports(Optional USB3.0).
System Control	Power LED*1 , Reset*1 , Power SW*1 , HDD LED*1 , NIC LED*2 , UID LED*1 , UID SW*1 , OH/FAN Fail LED*1 , Power Fail LED*1.
Application	Cloud storage, cloud computing, big data, security monitoring, LOTetc.

Product Features:

- 1.Conformed with EMC design standard to prevent from electromagnetic interference.
- 2.Support motherboard size up to 12" x 13", and 8*3.5"HDD bays, Standard PS2 power supply or redundant power supply.
- 3.The chassis has good ventilation system 3pcs 12038H ball bearing fans to make sure the system work steadily.