

The4thware Industrial Server

1U Hot-Swappable Industrial Server for ODM Purpose

T4WT-TT16510



PRODUCT SPECIFICATION

Specification	
Dimensions (mm)	437.5mm x 650mm x 44mm, standard 19" rackmount chassis.
Materials	1.0mm SGCC Zinc-Coated Steel.
Backplane	6Gb/s SATA backplane, with temperature control chipset, SGPIO.
Drivers bay	10 x 2.5" hot-swap drive bays.
Colour	Handle and lug are black, other steel colors.
Cooling Fan	Optional 4pcs 40mm fans position.
PSU form factor	1U standard power supply.
M/B form factor	Support MAX 12" x 13" motherboard.
Expansion Slot	1 full-height PCI/PCIE expansion slots.
Connector	Two front accessible USB2.0 ports.
System Control	Power LED*1, Reset*1, Power SW*1, HDD LED*1, NIC LED*2, UID LED*1, UID SW*1.
Application	Storage, security monitoring, cloud computing, LOT etc.

Product Features:

1. Conformed with EMC design standard to prevent from electromagnetic interference.
2. Support motherboard size up to 12" x 13", and 10 x 2.5" hot-swap drive bays, 1U standard power supply.
3. The chassis has good ventilation system 4pcs 40mm fans to make sure the system work steadily.