

The4thware Industrial Server

1U Hot-Swappable Industrial Server for ODM Purpose

T4WT-TS16504



PRODUCT SPECIFICATION

| Specification | |
|-----------------|---|
| Dimensions(mm) | 437.5mm x 650mm x 44mm, standard 19" rackmount chassis. |
| Materials | 1.0mm SGCC Zinc-Coated Steel. |
| Backplane | 6Gb/s SATA backplane, / 6Gb/s MINI SAS backplane,with temperature control chipset. / 12Gb/s MINI SAS backplane, with temperature control chipset. |
| Drivers bay | 4 x 3.5" hot-swap SATA (II or III) / SAS (II or III) 6Gb/s drive bays. |
| CD-ROM bays | 1 slim CD-ROM bay(Compatible with 2.5" HDD/SSD). |
| Cooling Fan | Optional 6pcs 40mm fan position, standard quotation with 4pcs 4028 AV C ball bearing fans. |
| PSU form factor | 1U standard power supply, length180-250mm. |
| M/B form factor | Support MAX 12" x 13" motherboard. |
| Expansion slot | 1 full-height PCI/PCIE expansion slots. |
| Connector | Two front accessible USB2.0 ports(Optional USB3.0). |
| System Control | Power LED*1 , Reset*1 , Power SW*1 , HDD LED*1 , NIC LED*2 , UID LED*1 , UID SW*1 , OH/FAN Fail LED*1 , Power Fail LED*1 |
| Application | Storage,security monitoring,cloud computing,LOTetc. |

Product Features:

- 1.Conformed with EMC design standard to prevent from electromagnetic interference.
- 2.Support motherboard size up to 12" x 13",and 4*3.5"HDD bays,1 slim CD-ROM , 1U standard power supply, length180-250mm.
- 3.The chassis has good ventilation system 4pcs 4028 AVC ball bearing fans to make sure the system work steadily.