

The4thware Industrial Server

1U Hot-Swappable Industrial Server for ODM Purpose

T4WT-TS15604



PRODUCT SPECIFICATION

Specification	
Dimensions(mm)	437.5mm x 560mm x 44mm, standard 19" rackmount chassis.
Materials	1.0mm SGCC Zinc-Coated Steel.
Backplane	6Gb/s SATA backplane, / 6Gb/s MINI SAS backplane,with temperature control chipset. / 12Gb/s MINI SAS backplane, with temperature control chipset.
Drivers bay	4 x 3.5" hot-swap SATA (II or III) / SAS (II or III) 6Gb/s drive bays.
CD-ROM bays	1 slim CD-ROM bay(Compatible with 2.5" HDD/SSD).
Cooling Fan	Optional 6pcs 40mm fan position, standard quotation with 4pcs 4028 AV C ball bearing fans.
PSU form factor	1U standard power supply.
M/B form factor	Support MAX 12" x 10.5" motherboard.
Expansion Slot	1 full-height PCI/PCIE expansion slots.
Connector	Two front accessible USB2.0 ports(Optional USB3.0).
System Control	Power LED*1 , Reset*1 , Power SW*1 , HDD LED*1 , NIC LED*2 , UID LED*1 , UID SW*1 , OH/FAN Fail LED*1 , Power Fail LED*1
Application	Storage,security monitoring,cloud computing,LOTEtc.

Product Features:

- 1.Conformed with EMC design standard to prevent from electromagnetic interference.
- 2.Support motherboard size up to 12" x 10.5",and 4*3.5"HDD bays,1 slim CD-ROM ,1U standard power supply.
- 3.The chassis has good ventilation system 4pcs 4028 AVC ball bearing fans to make sure the system work steadily.