

# The4thware Industrial Server

2U Hot-Swappable Industrial Server for ODM Purpose

T4WT-TT27825



PRODUCT SPECIFICATION

Specification	
Dimensions(mm)	438mm x 780mm x 88mm, standard 19" rackmount chassis.
Materials	1.0mm SGCC Zinc-Coated Steel.
Backplane	12GB/S Mini SAS backplane.
Driver bays	Support 25x 2.5" HDD/SDD drive bays on the front,2*2.5"HDD/SDD drive bays on the back.
Cooling Fan	4 x 8038mm fans
PSU form factor	Standard PSU2 CRPS power supply
M/B form factor	Support MAX 12" x 10.5" motherboard.
Expansion Slot	7 full-height PCI/PCIE expansion slots.
Connector	Two front accessible USB2.0 ports(Optional USB3.0), 1*VGA port.
System Control	Power LED*1 , Reset*1 , Power SW*1 , HDD LED*1 , NIC LED*2 , UID SW*1,OH/FAN Fail LED*1 , Power Fail LED*1
Application	Cloud storage, cloud computing, big data, security monitoring, LOTetc.

Product Features:

- 1.Conformed with EMC design standard to prevent from electromagnetic interference.
- 2.Support motherboard size up to 12" x 10.5", and 25x 2.5" HDD/SDD drive bays, Standard PSU2 CRPS power supply.
- 3.The chassis has good ventilation system 4 x 8038mm fans to make sure the system work steadily.